



## **TANNINS**


# ENARTISTAN CŒUR DE CHÊNE




#### COMPOSITION

Ellagic tannin extracted oak.

#### **GENERAL CHARACTERISTICS**





The use of EnartisTan Cœur de Chêne as a wine fining and stabilizing agent:

- prevents and treats the formation of reduction notes
- respects structure and organoleptic balance
- enhances oak notes in wines aged in barrels

### **APPLICATIONS**

During aging for:



- Fining of white and red wines
- Protein stabilization of white and rosé wines
- Prevention of hazes and oxidative phenomena due to iron and other metals
- Increased sensory cleanliness
- Prolong the life span of barrels
- Control and prevention of reductive aromas



#### DOSAGE

3 - 10 g/hL (0.25 - 0.8 lb/1000 gal).



## **INSTRUCTIONS FOR USE**

Dissolve EnartisTan Cœur de Chêne in a 1:10 ratio in water or wine while mixing continuously. Add to wine during a pump-over with a dosage pump or a Venturi tube.

Performing laboratory trials to evaluate the sensory impact of the tannins and in order to determine the best dosage is advised. It is best to add EnartisTan Cœur de Chêne in the first stages of ageing up until the last 1-2 weeks before bottling. If added close to bottling, it is important to evaluate the effect on filterability and protein and colloidal stability by completing preliminary laboratory trials.



## PACKAGING AND STORAGE CONDITIONS

1 kg

Sealed package: store in a cool, dry, well-ventilated area. Opened package: carefully reseal and store as indicated above.



Product approved for winemaking in accordance with Reg. (EU) 2019/934



Product approved for winemaking by the TTB:

Legal Limit: The residual amount of tannin shall not exceed 0.8 g/L in white wine and 3.0 g/L in red wine (in gallic acid). Only tannin which does not impart color may be used. Total tannin shall not be increased by more than 150 mg/L (in tannic acid).

The indications given here correspond to the current state of our knowledge and experience, however they do not relieve the user from compliance with safety and protection regulations or from improper use of the product.